



INFOSAT CO., LTD.

**FEATURE**

- ❑ RF shield zinc die cast housing, nickel-plated.
- ❑ All ports F-(f) connector, 75 Ω.
- ❑ Low insertion loss, high return loss .
- ❑ Two pieces of screws attached.
- ❑ Light weight and compact size.
- ❑ Grounding terminal provided.
- ❑ Option -PH : Adding plastic holder for the cable to pass through underneath the unit.
- ❑ Screening factor: 40-470 MHz ≥ 75 dB  
470-1000 MHz ≥ 65 dB

**SPECIFICATIONS**

Item Model	Insertion Loss (dB)				Mutual Isolation (dB)				Return Loss (dB)			
	5 – 40 MHz	40 – 470	470 – 860	860 – 1000	5 – 40	40 – 470	470 – 860	860 – 1000	5 – 40	40 – 470	470 – 860	860 – 1000
SPL-2772	3.5	3.7	3.8	4.0	30	30	30	25	22	22	20	20
SPL-2773	5.6	5.8	6.2	6.5	30	30	28	25	22	22	20	18
SPL-2774	6.8	7.0	7.8	8.0	30	30	28	25	22	22	20	18
SPL-2776	9.0	9.0	10.5	11.0	30	28	28	25	21	20	20	18

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

